

# STAR LED Downlights

## 150mm | 180mm




Model	Wattage	VEET	IPART	Lumens	Colour	Warranty
LPDL150T	16	TBA	TBA	3k-1,470   4k-1,760   5k-1,650	3 - 4 - 5k	3 years
LPDL180T	20	TBA	TBA	3k-1,800   4k-2,100   5k-1,930	3 - 4 - 5k	3 years

**TRI-COLOUR**  
3K-4K-5K

### Features & Benefits

- Easy to install
- TRI - Colour
- Integrated driver
- Dimmable with most systems
- Plug-top fitted
- SAA Approved
- SMD LED with a PMMA diffuser
- Up to 80% savings
- IP40
- 150mm cut out
- 180mm cut out
- IC - 4 Rated
- 3 year warranty period



TRI Switch Control



### Dimensions & Weight

Model	Width	Cut Out	Net Weight
LPDL150T	190mm	150mm	0.5kg
LPDL180T	225mm	180mm	0.6kg

### Technical Specifications

Voltage	Wattage	Beam Angle	Colour	Life Cycle
AC220/240V	16w / 20w	90°	3,000-4,000k-5,000k	50,000 Hrs
IP Rating	VEET/ESS/REES	Diffused	Dimmable	Heat Rating
IP40	TBA	Yes	Yes	-20°C to +45°C