

3w Emergency Spit Fire

Recessed and Surface Mount

Model	Wattage	Classification	Recessed	Lumens	Cut-Out	Warranty
LPEMGSF	3w	D63	Yes	280	40mm / 80mm	3 years
LPEMGSF-S	3w	D63	No	280	Surface	3 years



Features & Benefits

- Easy to install
- Lead and plug top fitted
- LiFePO4 Battery
- High quality LED driver
- 240 Lumens
- 3 hour battery back up
- 3 year warranty period
- SAA Approved
- 40mm & 80mm cut outs
- IP20 Rated
- Intergrated self test button
- 2 x lense optics included - Round & Oval
- Recessed & Surface options



Surface Mount Unit

Dimensions & Weight



Model	Diameter	Depth	Dimmable	Net Weight
LPEMSF	55mm / 140mm	30mm	NO	0.18kg
LPEMSF-S	148 x 148mm	33mm	NO	0.35kg

SPACING TABLE AND MOUNTING HEIGHTS – AS/NZS 2293.1:2018 (MINIMUM LIGHT LEVEL OF 0.2 LUX)														
Classification	2.1m	2.4m	2.7m	3.0m	3.3m	3.6m	4.0m	4.5m	5.0m	6.0m	7.0m	8.0m	9.0m	10.0m
D63	11.5	13.2	14.8	16.5	18.1	19.8	22	24.5	25.2	26.4	27.3	28	28.5	28.8
E63	9	10.3	11.6	12.9	14.1	15	16.1	17.4	18.6	20.7	22.6	24.1	25.5	26.6

Technical Specifications

Voltage 200-240VAC	Wattage 3w	Power Factor >0.3	Beam Angle 150°	Classification D63	Life Cycle 40,000 Hrs
IP Rating IP20	CCT 5,000k	CRI >80	Diffused No	Dim / DALI No - Option	Heat Rating 0°c to +45°c