


# SATIN Switchable High Bay



## TRI Wattage - BI Colour - High Lumens

Model	Wattage	CRI	Surge Protect	Lumens	Colour	Warranty
LPSATHB	100 / 150 / 200	80<	Yes	17,000 / 25,500 / 34,000	4,000k / 5,000k	5 Years *

170 + L/pw



Quick-Fit Motion Sensor  
Screws into place in 10 Seconds

### Features & Benefits

- TRI - wattage in one unit - Selected via a dip switch
- BI - colour - 4000k / 5000k
- Extruded Alloy lamp body
- In-built 6kV Surge Protection
- 1.2m lead with plug top included.
- Easy to install with O hook. Fixing bracket optional.
- Upto 170 LM/W
- 5 year Warranty
- Extra long life time expectancy with an extremely low case temperature.
- Quick-fix motion sensor options available - Installation takes 10 seconds.
- Trunnion mount available
- TM21 - L70 = 56,000 hours

### Dimensions & Weight



Model	Width	Height	Net Weight
LPSATHB	275mm	125mm	6.2kg

### Technical Specifications



Switchable Wattage - 100 / 150 / 200w

Switchable CCT - 4000k / 5000k

Voltage AC120/277V	Wattage 100w / 150w / 200w	Beam Angle 120°	Colour 4,000 / 5,000k	Life Cycle 56,000+ Hrs
IP Rating IP65	VEET/ESS/REES Pending	Accessories M-Sensor / PE Cell / Bracket	Dimmable Yes - Via M-Sensor	Ideal Op Temp -40°C to +50°C