

# RONIN Bollard Light

## Tri-colour / Quad-wattage



Model	Wattage	Type	Lumens	Colour (CCT)	Warranty
LPRBLT	4.5 / 7.5 / 11.3 / 15w	Bollard Top	450   750   1,130   1,500 Lm	3,000   4,000   5,000k	5 years
LPRBL500	(Lamp Body)	500mm Body	-	-	5 years
LPRBL1100	(Lamp Body)	1100mm Body	-	-	5 years



1,100mm High



500mm High

### Features & Benefits

- Wattage adjustable
- CCT Adjustable
- 2 different sizes available
- 100 lumen per watt
- Long life Driver
- IP66 Rated
- IK10 Rated
- Corrosion resistive, powder coated body
- Backed by a 5 year warranty period
- Mounting base plate included
- Architectural lamp design



Unique Curved Design

### Dimensions & Weight



Model	Length	Width	Spigot Connection	Net Weight
LPRBLT	100mm	135mm	50-62mm	3.00kg
LPRBL500	400mm	135mm	50-62mm	1.50kg
LPRBL1100	1000mm	135mm	50-62mm	3.50kg

### Technical Specifications

Voltage AC120-277V	Wattage 4.5 / 7.5 / 11.3 / 15w	Power Factor >0.90	Beam Angle A-Sym 180 degree	Colour Mixed	Life Cycle 60,000 Hrs
IP Rating IP66	Powder Coated Yes - Black (9017 RAL)	CRI >72	IK Rating IK10	Corrosion Rating C3	Heat Rating -30°C to +45°C

\* Please Note: Light Planet's warranty covers for defective products only. No incidentals like labor or hire cost shall be claimed from any party. Please read our T&C for further information.